

ECS4310-26T

Gigabit Ethernet Smart Switch



Product Overview

The Edge-Core web smart Gigabit Ethernet Switch ECS4310-26T is a new 24 ports Gigabit smart switch with 2 Gigabit SFP slots that bring the speed of Gigabit copper to the desktop with the added flexibility of fiber. ECS4310-26T enables networks of all sizes to introduce Gigabit Ethernet with management features targeted to meet the needs of the SMB network, and Gigabit to the desktop for power users. It provides a flexible web based management interface to enable the configuration of switch features, port settings including security, QoS with 8 queues, link aggregation and VLANs. These features can increase throughput and flexibility. Security is more important in next generation networks so this switch has added security features to protect your network.

Key Features and Benefits

Performance and Scalability

It's a great entry level managed with 52Gbps switching capacity delivers wire-speed switching performance to take full advantage of existing high-performance on PCs and laptops by significantly improving the responsiveness of applications and file transfer times.

The device also has two Gigabit Ethernet combo ports for uplink flexibility, allowing copper or fiber uplinks port for high speed uplinks to servers or backbones.

Continuous Availability

IEEE 802.1w Rapid Spanning Tree Protocol provides a loop-free network and redundant links to the core network with rapid convergence, to ensure faster recovery from failed links, enhancing overall network stability and reliability.

IEEE 802.1s Multiple Spanning Tree Protocol runs STP per VLAN base, providing Layer 2 load sharing on redundant links up to 8 instances.

IEEE802.3ad Link Aggregation Control Protocol (LACP) increases bandwidth by automatically aggregating several physical links together as a logical trunk and providing load balancing and fault tolerance for uplink connections.

IGMP snooping prevents flooding of IP multicast traffic and limits bandwidth intensive video traffic to only the subscribers.

The IEEE 802.1Q-in-Q VLAN Tag is purpose to expand the VLAN space by tagging the tagged packets, thus producing a double-tagged frame.

Comprehensive QoS

8 egress queues per port enable differentiated management of up to 8 traffic types.

Traffic is prioritized according to 802.1p, DSCP, IP precedence and TCP/UDP port number, giving optimal performance to real-time applications such as voice and video.

Asymmetric bidirectional rate-limiting, per port or per traffic class, preserves network bandwidth and allowing maximum control of network resources.

Enhanced Security

Port Security ensures access to switch ports based on MAC address, limits the total number of devices from using a switch port and protects against MAC flooding attacks.

IEEE 802.1x port-based or MAC-based access control ensures all users are authorized before being granted access to the network. User authentication is carried out using any standard-based dynamic VLAN assignment with RADIUS server by guest VLAN.

Simple Management

Embedded user friendly web interface helps users quickly and simply configure switches.

It's also supports SNMP V1 to be managed and control SNMP network station.

Cable diagnostics for diagnose any cable faults (Short, Open etc..) and feedback a distance to the fault.

LLDP (Link Layer Discovery Protocol) enables administrator to monitor what device is attached to the switch.

